

◆ **Shape/外觀:**



◆ **Specifications /規格表:**

Catalog Listing / 型號	<b>PK3-DU30N</b> <b>PK3-DU30P</b>	<b>PK3-R2N</b> <b>PK3-R2P</b>	<b>PK3-5N</b> <b>PK3-5P</b>
	<b>PK3-DU30ND</b> <b>PK3-DU30PD</b>	<b>PK3-R2ND</b> <b>PK3-R2PD</b>	<b>PK3-5ND</b> <b>PK3-5PD</b>
Description / 檢出方式	Diffuse reflection / 擴散反射式	Retro reflection/ 鏡片反射式	Through beam / 對照式
Sensing distance / 檢出距離	30 cm	2M	5M
Output method / 輸出模式	NPN.NO / PNP.NO		
Response time / 反應時間	1.5 ms Max.		
Light emitter / 發光源	850 nm.	940 nm.	850 nm.
Operating voltage / 工作電壓	DC: 12 ~ 24 VDC		
Current consumption / 消耗電流	25 mA Max.		40 mA Max.
Output current / 輸出電流	24 VDC 100mA max.		
Insulation resistance / 隔離阻抗	20M Ω Min. 500VDC		
Dielectric strength / 絕緣耐壓	1000VAC for 1min.		
Ambient humidity / 工作溼度範圍	35%~85% RH		
Weight / 重量	Approx 60g		
Operating temperature/工作溫度範圍	- 20 °C ~ + 60 °C		
Housing material / 外觀材質	ABS		
Wiring method / 出線方式	<b>PK3-□N/P:</b> Ø4.2 × 2 M / 4-cores <b>PK3-□D:</b> M8 pigtailed type/M8 接頭15cm 電線式		
Protection degree / 防水等級	IP65		

◆ **Dimensions /尺寸圖:**

