



Output method / 輸出模式	NPN.NO	SC0401-N	SC0501-N
	NPN.NC	SC0401-N2	SC0501-N2
	PNP.NO	SC0401-P	SC0501-P
	PNP.NC	SC0401-P2	SC0501-P2
	NPN.NO/NC	—	—
	PNP.NO/NC	—	—
	SCR.NO	—	—
SCR.NC	—	—	
Sensing surface / 檢測方向	Top surface / 前方		
Hysteresis / 遲滯	≅ 10 % of sensing distance		
Sensing distance / 檢出距離	0.8 mm		
Response frequency / 反應頻率	2K Hz		
Recommended distance / 建議距離	0 to 0.5 mm		
Standard sensing object / 標準檢測物	Iron/金屬感應物(鐵)		
Operating voltage / 工作電壓	DC: 6 ~ 30 VDC		
Current consumption / 消耗電流	≅ 10 mA no-load		
Output current / 輸出電流	150 mA Max		
Leakage current / 漏電流	≅ 1.1 mA no-load		
Residual voltage / 殘餘電壓	≅ 1.4 VDC		
Operating temperature / 工作溫度範圍	- 25 °C ~ + 70 °C		
Wiring method / 出線方式	Ø3 x 2m x 3 cores)		
Protection degree / 防水等級	IP 66		

