



| NTL-FF120 Filter with Fan                                                       |                   |                       |                             |
|---------------------------------------------------------------------------------|-------------------|-----------------------|-----------------------------|
| Enclosure Cut-out                                                               | 92×92mm           |                       |                             |
| Art No.                                                                         | Operating voltage | Air volume, free flow | Air volume with exit filter |
| 860204                                                                          | AC 230V, 50/60Hz  | 39/48m³/h             | 32/41m³/h                   |
| 860205                                                                          | AC 115V, 50/60Hz  | 39/48m³/h             | 32/41m³/h                   |
| 120VAC, 230VAC, 120VAC&230VAC, 400VAC, 12VDC, 24VDC, 48VDC can be customer made |                   |                       |                             |




| NTL-F120 Exit Filter |                    |
|----------------------|--------------------|
| Enclosure Cut-out    | 92×92mm            |
| Art No.              | Depth in enclosure |
| 860206               | 24mm               |




| NTL-FF152 Filter with Fan                                                       |                   |                       |                             |
|---------------------------------------------------------------------------------|-------------------|-----------------------|-----------------------------|
| Enclosure Cut-out                                                               | 125×125mm         |                       |                             |
| Art No.                                                                         | Operating voltage | Air volume, free flow | Air volume with exit filter |
| 860207                                                                          | AC 230V, 50/60Hz  | 138/162m³/h           | 100/120m³/h                 |
| 860208                                                                          | AC 115V, 50/60Hz  | 138/162m³/h           | 100/120m³/h                 |
| 120VAC, 230VAC, 120VAC&230VAC, 400VAC, 12VDC, 24VDC, 48VDC can be customer made |                   |                       |                             |




| NTL-F152 Exit Filter |                    |
|----------------------|--------------------|
| Enclosure Cut-out    | 125×125mm          |
| Art No.              | Depth in enclosure |
| 860209               | 24mm               |



| NTL-FF204 Filter with Fan                                                       |                   |                       |                             |
|---------------------------------------------------------------------------------|-------------------|-----------------------|-----------------------------|
| Enclosure Cut-out                                                               | 177×177mm         |                       |                             |
| Art No.                                                                         | Operating voltage | Air volume, free flow | Air volume with exit filter |
| 860210                                                                          | AC 230V, 50/60Hz  | 138/162m³/h           | 100/120m³/h                 |
| 860211                                                                          | AC 115V, 50/60Hz  | 138/162m³/h           | 100/120m³/h                 |
| 120VAC, 230VAC, 120VAC&230VAC, 400VAC, 12VDC, 24VDC, 48VDC can be customer made |                   |                       |                             |




| NTL-F204 Exit Filter |                    |
|----------------------|--------------------|
| Enclosure Cut-out    | 177×177mm          |
| Art No.              | Depth in enclosure |
| 860212               | 24mm               |




| NTL-FF255 Filter with Fan                                                       |                   |                       |                             |
|---------------------------------------------------------------------------------|-------------------|-----------------------|-----------------------------|
| Enclosure Cut-out                                                               | 223×223mm         |                       |                             |
| Art No.                                                                         | Operating voltage | Air volume, free flow | Air volume with exit filter |
| 860213                                                                          | AC 230V, 50/60Hz  | 299/336m³/h           | 210/246m³/h                 |
| 860214                                                                          | AC 115V, 50/60Hz  | 299/336m³/h           | 210/246m³/h                 |
| 120VAC, 230VAC, 120VAC&230VAC, 400VAC, 12VDC, 24VDC, 48VDC can be customer made |                   |                       |                             |



| NTL-F255 Exit Filter |                    |
|----------------------|--------------------|
| Enclosure Cut-out    | 223×223mm          |
| Art No.              | Depth in enclosure |
| 860215               | 24mm               |



| NTL-FF323 Filter with Fan                                                       |                   |                       |                             |
|---------------------------------------------------------------------------------|-------------------|-----------------------|-----------------------------|
| Enclosure Cut-out                                                               | 291×291mm         |                       |                             |
| Art No.                                                                         | Operating voltage | Air volume, free flow | Air volume with exit filter |
| 860216                                                                          | AC 230V, 50/60Hz  | 780/890m³/h           | 680/880m³/h                 |
| 860217                                                                          | AC 115V, 50/60Hz  | 780/890 CFM           | 680/880m³/h                 |
| 120VAC, 230VAC, 120VAC&230VAC, 400VAC, 12VDC, 24VDC, 48VDC can be customer made |                   |                       |                             |



| NTL-F323 Exit Filter |                    |
|----------------------|--------------------|
| Enclosure Cut-out    | 291×291mm          |
| Art No.              | Depth in enclosure |
| 860218               | 24mm               |



With Fan

| NTL-FF152-W Filter with Rain-Resistance Hood                                    |                   |                       |                             |
|---------------------------------------------------------------------------------|-------------------|-----------------------|-----------------------------|
| Enclosure Cut-out                                                               | 125×125mm         |                       |                             |
| Art No.                                                                         | Operating voltage | Air volume, free flow | Air volume with exit filter |
| 862250                                                                          | AC 230V, 50/60Hz  | 138/162m³/h           | 100/120m³/h                 |
| 862251                                                                          | AC 115V, 50/60Hz  | 138/162m³/h           | 100/120m³/h                 |
| 120VAC, 230VAC, 120VAC&230VAC, 400VAC, 12VDC, 24VDC, 48VDC can be customer made |                   |                       |                             |



Without Fan

| NTL-F152-W Filter with Rain-Resistance Hood |                    |
|---------------------------------------------|--------------------|
| Enclosure Cut-out                           | 125×125mm          |
| Art No.                                     | Depth in enclosure |
| 862235                                      | 24mm               |



| NTL-FFL120 Filter with Fan |                   |                       |                             |
|----------------------------|-------------------|-----------------------|-----------------------------|
| Enclosure Cut-out          | 92×92mm           |                       |                             |
| Art No.                    | Operating voltage | Air volume, free flow | Air volume with exit filter |
| 862079                     | AC 230V, 50/60Hz  | 19m³/h                | 13m³/h                      |
| 862084                     | AC 115V, 50/60Hz  | 23m³/h                | 16m³/h                      |

120VAC, 230VAC, 120VAC&230VAC, 400VAC, 12VDC, 24VDC, 48VDC can be customer made



| NTL-FL120 Exit Filter |                    |
|-----------------------|--------------------|
| Enclosure Cut-out     | 92×92mm            |
| Art No.               | Depth in enclosure |
| 862074                | 29mm               |



| NTL-FFL152 Filter with Fan |                   |                       |                             |
|----------------------------|-------------------|-----------------------|-----------------------------|
| Enclosure Cut-out          | 125×125mm         |                       |                             |
| Art No.                    | Operating voltage | Air volume, free flow | Air volume with exit filter |
| 862080                     | AC 230V, 50/60Hz  | 52m³/h                | 42m³/h                      |
| 862085                     | AC 115V, 50/60Hz  | 62m³/h                | 51m³/h                      |

120VAC, 230VAC, 120VAC&230VAC, 400VAC, 12VDC, 24VDC, 48VDC can be customer made



| NTL-FL152 Exit Filter |                    |
|-----------------------|--------------------|
| Enclosure Cut-out     | 125×125mm          |
| Art No.               | Depth in enclosure |
| 862075                | 35mm               |



| NTL-FFL204 Filter with Fan |                   |                       |                             |
|----------------------------|-------------------|-----------------------|-----------------------------|
| Enclosure Cut-out          | 176×176mm         |                       |                             |
| Art No.                    | Operating voltage | Air volume, free flow | Air volume with exit filter |
| 862081                     | AC 230V, 50/60Hz  | 170m³/h               | 123m³/h                     |
| 862086                     | AC 115V, 50/60Hz  | 204m³/h               | 187m³/h                     |

120VAC, 230VAC, 120VAC&230VAC, 400VAC, 12VDC, 24VDC, 48VDC can be customer made



| NTL-FL204 Exit Filter |                    |
|-----------------------|--------------------|
| Enclosure Cut-out     | 176×176mm          |
| Art No.               | Depth in enclosure |
| 862076                | 43mm               |



| NTL-FFL255 Filter with Fan |                   |                       |                             |
|----------------------------|-------------------|-----------------------|-----------------------------|
| Enclosure Cut-out          | 223×223mm         |                       |                             |
| Art No.                    | Operating voltage | Air volume, free flow | Air volume with exit filter |
| 862082                     | AC 230V, 50/60Hz  | 305m³/h               | 210m³/h                     |
| 862087                     | AC 115V, 50/60Hz  | 332m³/h               | 293m³/h                     |

120VAC, 230VAC, 120VAC&230VAC, 400VAC, 12VDC, 24VDC, 48VDC can be customer made



| NTL-FL255 Exit Filter |                    |
|-----------------------|--------------------|
| Enclosure Cut-out     | 223×223mm          |
| Art No.               | Depth in enclosure |
| 862077                | 46mm               |



| NTL-FFL323 Filter with Fan |                   |                       |                             |
|----------------------------|-------------------|-----------------------|-----------------------------|
| Enclosure Cut-out          | 291×291mm         |                       |                             |
| Art No.                    | Operating voltage | Air volume, free flow | Air volume with exit filter |
| 862083                     | AC 230V, 50/60Hz  | 433m³/h               | 373m³/h                     |
| 862088                     | AC 115V, 50/60Hz  | 394m³/h               | 339m³/h                     |

120VAC, 230VAC, 120VAC&230VAC, 400VAC, 12VDC, 24VDC, 48VDC can be customer made



| NTL-FL323 Exit Filter |                    |
|-----------------------|--------------------|
| Enclosure Cut-out     | 291×291mm          |
| Art No.               | Depth in enclosure |
| 862078                | 50mm               |



| Filter with Rain-Resistance Hood |                    |                                                |
|----------------------------------|--------------------|------------------------------------------------|
| Enclosure Cut-out                | 125×125mm          |                                                |
| Art No.                          | Model              | Description                                    |
| 862772                           | NTL-FF125-W 230VAC | Filter Fan with Rain-Resistance Hood, with Fan |
| 862773                           | NTL-FF125-W 120VAC | Filter Fan with Rain-Resistance Hood, with Fan |

120VAC, 230VAC, 120VAC&230VAC, 400VAC, 12VDC, 24VDC, 48VDC can be customer made



| Filter with Rain-Resistance Hood |            |                                                    |
|----------------------------------|------------|----------------------------------------------------|
| Enclosure Cut-out                | 125×125mm  |                                                    |
| Art No.                          | Model      | Description                                        |
| 862771                           | NTL-F125-W | Exit Filter with Rain-Resistance Hood, without fan |



| NTL-SFF106 Filter with Fan |                   |                       |                             |
|----------------------------|-------------------|-----------------------|-----------------------------|
| Enclosure Cut-out          | 92×92mm           |                       |                             |
| Art No.                    | Operating voltage | Air volume, free flow | Air volume with exit filter |
| 861627                     | AC 230V, 50/60Hz  | 39/48m³/h             | 32/41m³/h                   |
| 861659                     | AC 115V, 50/60Hz  | 39/48m³/h             | 32/41m³/h                   |

120VAC, 230VAC, 120VAC&230VAC, 400VAC, 12VDC, 24VDC, 48VDC can be customer made



| NTL-SF106 Exit Filter |                    |
|-----------------------|--------------------|
| Enclosure Cut-out     | 92×92mm            |
| Art No.               | Depth in enclosure |
| 861616                | 26mm               |



| NTL-SFF150 Filter with Fan |                   |                       |                             |
|----------------------------|-------------------|-----------------------|-----------------------------|
| Enclosure Cut-out          | 125×125mm         |                       |                             |
| Art No.                    | Operating voltage | Air volume, free flow | Air volume with exit filter |
| 861628                     | AC 230V, 50/60Hz  | 138/162m³/h           | 100/120m³/h                 |
| 861660                     | AC 115V, 50/60Hz  | 100/120m³/h           | 100/120m³/h                 |

120VAC, 230VAC, 120VAC&230VAC, 400VAC, 12VDC, 24VDC, 48VDC can be customer made



| NTL-SF150 Exit Filter |                    |
|-----------------------|--------------------|
| Enclosure Cut-out     | 125×125mm          |
| Art No.               | Depth in enclosure |
| 861617                | 32mm               |



| NTL-SFF200 Filter with Fan |                   |                       |                             |
|----------------------------|-------------------|-----------------------|-----------------------------|
| Enclosure Cut-out          | 176×176mm         |                       |                             |
| Art No.                    | Operating voltage | Air volume, free flow | Air volume with exit filter |
| 862892                     | AC 230V, 50/60Hz  | 200m³/h               | 150m³/h                     |
| 862896                     | AC 115V, 50/60Hz  | 204m³/h               | 187m³/h                     |

120VAC, 230VAC, 120VAC&230VAC, 400VAC, 12VDC, 24VDC, 48VDC can be customer made



| NTL-SF200 Exit Filter |                    |
|-----------------------|--------------------|
| Enclosure Cut-out     | 176×176mm          |
| Art No.               | Depth in enclosure |
| 862888                | 24mm               |



| NTL-SFF250 Filter with Fan |                   |                       |                             |
|----------------------------|-------------------|-----------------------|-----------------------------|
| Enclosure Cut-out          | 223×223mm         |                       |                             |
| Art No.                    | Operating voltage | Air volume, free flow | Air volume with exit filter |
| 860213                     | AC 230V, 50/60Hz  | 380m³/h               | 310m³/h                     |
| 860214                     | AC 115V, 50/60Hz  | 400m³/h               | 350m³/h                     |

120VAC, 230VAC, 120VAC&230VAC, 400VAC, 12VDC, 24VDC, 48VDC can be customer made



| NTL-SF250 Exit Filter |                    |
|-----------------------|--------------------|
| Enclosure Cut-out     | 223×223mm          |
| Art No.               | Depth in enclosure |
| 860215                | 24mm               |



| NTL-SFF322 Filter with Fan |                   |                       |                             |
|----------------------------|-------------------|-----------------------|-----------------------------|
| Enclosure Cut-out          | 291×291mm         |                       |                             |
| Art No.                    | Operating voltage | Air volume, free flow | Air volume with exit filter |
| 862912                     | AC 230V, 50/60Hz  | 480m³/h               | 420m³/h                     |
| 862913                     | AC 115V, 50/60Hz  | 510m³/h               | 450m³/h                     |

120VAC, 230VAC, 120VAC&230VAC, 400VAC, 12VDC, 24VDC, 48VDC can be customer made



| NTL-SF322 Exit Filter |                    |
|-----------------------|--------------------|
| Enclosure Cut-out     | 291×291mm          |
| Art No.               | Depth in enclosure |
| 862889                | 24mm               |



| Etra Frame |           |                                                  |
|------------|-----------|--------------------------------------------------|
| Material   | Plastic   |                                                  |
| Art No.    | Model     | Match Filter Size                                |
| 861001     | NTL-AF204 | Other airflow protection for the model NTL-FF204 |
| 861002     | NTL-AF255 | Other airflow protection for the model NTL-FF255 |
| 861003     | NTL-AF323 | Other airflow protection for the model NTL-FF323 |



| Filter Mat  |                                                         |                       |
|-------------|---------------------------------------------------------|-----------------------|
| Normal Type | G4 , For special requirement, can According to customer |                       |
| Feature     | Purify for air, Easy to change and clean                |                       |
| Model       | Mat Size                                                | Match Fan Filter Size |
| NTL-F120M   | 86 x 86mm                                               | 120 x 120mm filter    |
| NTL-F152M   | 118 x 118mm                                             | 152 x 152mm filter    |
| NTL-F204M   | 171 x 171mm                                             | 204 x 204mm filter    |
| NTL-F255M   | 223 x 223mm                                             | 255 x 255mm filter    |
| NTL-F323M   | 286 x 286mm                                             | 323 x 323mm filter    |

**LC 013 Airflow Monitor**

|                   |                     |               |
|-------------------|---------------------|---------------|
| Operating Voltage | 240VAC/DC, 60VDC    |               |
| Contact Type      | Reed/magnet contact |               |
| Protection Class  | IP20                |               |
| Approvals         | CE, RoHS, Patent    |               |
| Art. No. (NC)     | Art. No. (NO)       | Dimensions    |
| 01300.0-00        | 01300.1-00          | 34×17.5×7.5mm |

**LCF 013 Airflow Monitor**

|                   |                     |              |
|-------------------|---------------------|--------------|
| Operating Voltage | 240VAC/DC, 60VDC    |              |
| Contact Type      | Reed/magnet contact |              |
| Protection Class  | IP20                |              |
| Approvals         | CE, RoHS, Patent    |              |
| Art. No. (NC)     | Art. No. (NO)       | Dimensions   |
| 01301.0-00        | 01301.1-00          | 80×88×10.5mm |
| 01302.0-00        | 01302.1-00          | 92×92×10mm   |
| 01303.0-00        | 01303.1-00          | 120×120×10mm |

**Plastic Guard for Fan**


|          |          |                        |
|----------|----------|------------------------|
| Material | Plastic  |                        |
| Art No.  | Model    | Guard for Fan Size of  |
| 861139   | NTL-FG80 | 80×80×25mm, 80×80×38mm |

**Plastic Guard for Fan**


|          |          |                        |
|----------|----------|------------------------|
| Material | Plastic  |                        |
| Art No.  | Model    | Guard for Fan Size of  |
| 861140   | NTL-FG92 | 92×92×25mm, 92×92×38mm |

**Plastic Guard for Fan**


|          |           |                            |
|----------|-----------|----------------------------|
| Material | Plastic   |                            |
| Art No.  | Model     | Guard for Fan Size of      |
| 861141   | NTL-FG120 | 120×120×25mm, 120×120×38mm |

**Plastic Guard for Fan**


|          |           |                         |
|----------|-----------|-------------------------|
| Material | Plastic   |                         |
| Art No.  | Model     | Guard for Fan Size of   |
| 861142   | NTL-FG170 | 172×150×51mm, Ø172×55mm |

**Plastic Guard for Fan**

|          |           |                       |
|----------|-----------|-----------------------|
| Material | Plastic   |                       |
| Art No.  | Model     | Guard for Fan Size of |
| 861143   | NTL-FG180 | 180×180×65mm          |

**Plastic Guard for Fan**

|          |           |                       |
|----------|-----------|-----------------------|
| Material | Plastic   |                       |
| Art No.  | Model     | Guard for Fan Size of |
| 861144   | NTL-FG200 | 200×200×60mm          |

**Plastic Guard for Fan**

|          |           |                         |
|----------|-----------|-------------------------|
| Material | Plastic   |                         |
| Art No.  | Model     | Guard for Fan Size of   |
| 861145   | NTL-FG225 | 225×225×80mm, Ø222×60mm |

**NTL-F80B/120B Filter**

|                   |                                        |                  |
|-------------------|----------------------------------------|------------------|
| Material          | ABS                                    |                  |
| Scope             | Room temperature from -10 to 55 degree |                  |
| Color             | Black                                  |                  |
| Dust removal rate | 89%                                    |                  |
| IP Code           | IP40                                   |                  |
| Art. No.          | Model                                  | Size             |
| 861145            | NTL-F80B                               | 80 x 80 x 10mm   |
| 861146            | NTL-F120B                              | 120 x 120 x 10mm |

**DA 084 Pressure Compensation Device**

|                  |                             |                  |
|------------------|-----------------------------|------------------|
| Mounting         | PG 29 thread with union nut |                  |
| Torque           | 5Nm (max. 10Nm)             |                  |
| Sealing          | Sealing gasket NBR          |                  |
| Air Interface    | Approx. 7cm <sup>2</sup>    |                  |
| Dimensions       | Ø65.5×30.5mm                |                  |
| Fitting Position | Vertical                    |                  |
| Art No.          | Protection type             | Weight (approx.) |
| 08400.0-04       | IP55                        | 31g              |


**DA 284 Pressure Compensation Device**

|                  |                         |                  |
|------------------|-------------------------|------------------|
| Mounting         | Thread M40×1.5 with nut |                  |
| Torque           | 5Nm (max. 10Nm)         |                  |
| Sealing          | Sealing gasket NBR      |                  |
| Filter           | Waterproof membrane     |                  |
| Dimensions       | Ø60×37mm                |                  |
| Fitting Position | Vertical                |                  |
| Art No.          | Protection type         | Weight (approx.) |
| 28400.0-01       | IP66                    | 45g              |




**NLT-DP01 Documents Pocket**


|                  |                                                              |
|------------------|--------------------------------------------------------------|
| Material         | ABS according to RoHS                                        |
| Color            | Similar to RAL 7035, also can be customer-made for the color |
| Installation Way | Screw mounting or adhesive tape mounting                     |
| Weight can carry | 5KGS.                                                        |
| Size             | 234 x 278 x 40mm                                             |

**SF 095 DIN Rail**

|                    |                            |                  |
|--------------------|----------------------------|------------------|
| Material           | Plastic Type or Metal Type |                  |
| Thickness          | Can be different           |                  |
| Width              | Can be different           |                  |
| Length             | Can be different           |                  |
| Fireproof Material |                            |                  |
| Art No.            | 1 packing unit             | Weight (approx.) |
| 09510.0-01         | 5 pieces                   | 60g (12g/pc.)    |

**LED 025**


|                            |                                   |                   |
|----------------------------|-----------------------------------|-------------------|
| Operating Voltage          | 48-265VAC/DC(min. 48V, max. 265V) |                   |
| Service Life               | 60,000h at 20°C (68°F)            |                   |
| Protection Class           | IP20 / II(Double Insulated)       |                   |
| Art No.<br>(Magnet fixing) | Art No.<br>(Screw fixing)         | Operating Voltage |
| 02540.0-00                 | 02540.0-01                        | 48V-265VAC/DC     |

**LED 025-C**


|                            |                                   |                   |
|----------------------------|-----------------------------------|-------------------|
| Operating Voltage          | 48-265VAC/DC(min. 48V, max. 265V) |                   |
| Service Life               | 60,000h at 20°C (68°F)            |                   |
| Protection Class           | IP20 / II(Double Insulated)       |                   |
| Art No.<br>(Magnet fixing) | Art No.<br>(Screw fixing)         | Operating Voltage |
| 862769                     | 862770                            | 48V-265VAC/DC     |

**SD 035 Electrical Socket**

|                  |                                                              |                   |
|------------------|--------------------------------------------------------------|-------------------|
| Connection       | 3 x pressure clamps for stranded and rigid wire 0.5 - 2.5mm² |                   |
| Mounting         | Clip for 35mm DIN rail, EN 60715                             |                   |
| Casing           | Plastic according to UL94 V-0, light grey                    |                   |
| Dimensions       | 92×62×48mm                                                   |                   |
| Fitting position | Variable                                                     |                   |
| Protection class | IP20 / I(Earthed)                                            |                   |
| Art No.          | Nominal current                                              | Operating Voltage |
| 03504.0-00       | 15A                                                          | 125V              |

**DS 013 Door Switch**

|                    |                                           |               |
|--------------------|-------------------------------------------|---------------|
| Switching Capacity | 250VAC, 8 (1.5) A                         |               |
| Service Life       | VDE: > 10,000 cycles / UL: > 6,000 cycles |               |
| Mounting           | screw fixing (M5)                         |               |
| Art No.            | Model                                     | Suitable wire |
| 01350.0-00         | Change-over (CO)                          | 0.75~1mm²     |
| 01351.0-00         | Normally closed (NC)                      | 0.75~1.5mm²   |
| 01352.0-00         | Normally open (NO)                        | 0.75~1.5mm²   |

**Female Connectors / Male Connectors**

|              |                  |              |
|--------------|------------------|--------------|
| Voltage type | Power input      |              |
| Art No.      | Model            | Voltage type |
| 264057       | Female connector | AC           |
| 264058       | Male connector   | AC           |

**NLT-MMB Multiple Mounting Bracket**

Confirm to RoHS  
Fit to different angle, different place, different size products installation


Fast and easy for fixing

Endurance high temperature and low temperature

|         |             |                  |
|---------|-------------|------------------|
| Art No. | Size        | Weight (approx.) |
| NLT-MMB | 136.5×190mm | -                |

**Heaters Fixing Parts**

|          |                |                  |
|----------|----------------|------------------|
| Material | Aluminum alloy |                  |
| Art No.  | Size           | Weight (approx.) |
| -        | -              | -                |
| -        | -              | -                |
| -        | -              | -                |

**Heaters Fixing Parts**


|          |       |                  |
|----------|-------|------------------|
| Material | Steel |                  |
| Art No.  | Size  | Weight (approx.) |
| -        | -     | -                |

**NA 8025 Fan**


|            |             |          |       |
|------------|-------------|----------|-------|
| Size       | 80×80×25mm  |          |       |
| Model      | Voltage (V) | Air Flow |       |
|            |             | M³/hr    | CFM   |
| NA8025HA1B | 100~125     | 32/39    | 19/23 |
| NA8025HA2B | 200~240     | 32/39    | 19/23 |
| NA8025MA1B | 100~125     | 24/32    | 14/19 |
| NA8025MA2B | 200~240     | 24/32    | 14/19 |

**NA 8038 Fan**


|            |             |          |       |
|------------|-------------|----------|-------|
| Size       | 80×80×38mm  |          |       |
| Model      | Voltage (V) | Air Flow |       |
|            |             | M³/hr    | CFM   |
| NA8038HA1B | 100~125     | 39/48    | 28/32 |
| NA8038HA2S | 200~240     | 39/48    | 28/32 |

**NA 9025 Fan**


|               |             |                    |       |
|---------------|-------------|--------------------|-------|
| Size          | 92×92×25mm  |                    |       |
| Model         | Voltage (V) | Air Flow           |       |
|               |             | M <sup>3</sup> /hr | CFM   |
| NA9225HA1S(B) | 100~125     | 47/58              | 28/34 |
| NA9225HA2S(B) | 200~240     | 47/58              | 28/34 |
| NA9225MA1S(B) | 100~125     | 37/45              | 22/26 |
| NA9225MA2S(B) | 200~240     | 37/45              | 22/26 |

**NA 9038 Fan**


|               |             |                    |       |
|---------------|-------------|--------------------|-------|
| Size          | 92×92×38mm  |                    |       |
| Model         | Voltage (V) | Air Flow           |       |
|               |             | M <sup>3</sup> /hr | CFM   |
| NA9238HA1S(B) | 100~125     | 66/78              | 38/46 |
| NA9238HA2S(B) | 200~240     | 72/85              | 38/46 |
| NA9238MA1S(B) | 100~125     | 63/70              | 37/41 |
| NA9238MA2S(B) | 200~240     | 65/75              | 37/41 |

**NA 11025 Fan**

|                |              |                    |       |
|----------------|--------------|--------------------|-------|
| Size           | 110×110×25mm |                    |       |
| Model          | Voltage (V)  | Air Flow           |       |
|                |              | M <sup>3</sup> /hr | CFM   |
| NA11025HA1S(B) | 100~125      | 84/100             | 49/59 |
| NA11025HA2S(B) | 200~240      | 84/100             | 49/59 |
| NA11025MA1S(B) | 100~125      | 70/84              | 41/49 |
| NA11025MA2S(B) | 200~240      | 70/84              | 41/49 |

**NA 12025 Fan**

|                |              |                    |       |
|----------------|--------------|--------------------|-------|
| Size           | 120×120×25mm |                    |       |
| Model          | Voltage (V)  | Air Flow           |       |
|                |              | M <sup>3</sup> /hr | CFM   |
| NA12025HA1S(B) | 100~125      | 96/112             | 57/66 |
| NA12025HA2S(B) | 200~240      | 96/112             | 57/66 |
| NA12025MA1S(B) | 100~125      | 76/95              | 45/56 |
| NA12025MA2S(B) | 200~240      | 76/95              | 45/56 |

**NA 12038 Fan**

|                |              |                    |       |
|----------------|--------------|--------------------|-------|
| Size           | 120×120×38mm |                    |       |
| Model          | Voltage (V)  | Air Flow           |       |
|                |              | M <sup>3</sup> /hr | CFM   |
| NA12038HA1B(S) | 100~125      | 138/162            | 82/95 |
| NA12038HA2B(S) | 200~240      | 138/162            | 82/95 |
| NA12038HA3B(S) | 380          | 138/162            | 82/95 |

**NA 17050 Fan**

|                |              |                    |         |
|----------------|--------------|--------------------|---------|
| Size           | 172×150×50mm |                    |         |
| Model          | Voltage (V)  | Air Flow           |         |
|                |              | M <sup>3</sup> /hr | CFM     |
| NA17050HA1B(S) | 100~125      | 299/336            | 176/198 |
| NA17050HA2B(S) | 200~240      | 299/336            | 176/198 |
| NA17050HA3B(S) | 200~240      | 299/336            | 176/198 |

**NA 1725 Fan**

|               |              |                    |         |
|---------------|--------------|--------------------|---------|
| Size          | 172×172×51mm |                    |         |
| Model         | Voltage (V)  | Air Flow           |         |
|               |              | M <sup>3</sup> /hr | CFM     |
| NA1725HA1B(S) | 100~125      | 299/336            | 176/198 |
| NA1725HA2B(S) | 200~240      | 299/336            | 176/198 |
| NA1725HA3B(S) | 380          | 299/336            | 176/198 |

**NA 18065 Fan**

|               |              |                    |         |
|---------------|--------------|--------------------|---------|
| Size          | 180×180×65mm |                    |         |
| Model         | Voltage (V)  | Air Flow           |         |
|               |              | M <sup>3</sup> /hr | CFM     |
| NA18065HA1B-C | 100~125      | 586/671            | 345/395 |
| NA18065HA2B-C | 200~240      | 586/671            | 345/395 |

**NA 20060 Fan**

|                 |              |                    |         |
|-----------------|--------------|--------------------|---------|
| Size            | 200×200×60mm |                    |         |
| Model           | Voltage (V)  | Air Flow           |         |
|                 |              | M <sup>3</sup> /hr | CFM     |
| NA20060HA1B-W-C | 100~125      | 780/890            | 460/530 |
| NA20060HA2B-W-C | 200~240      | 780/890            | 460/530 |
| NA20060HA3B-W-C | 380          | 780/890            | 460/530 |

**NA 22060 Fan**

|                |              |                    |         |
|----------------|--------------|--------------------|---------|
| Size           | 220×220×60mm |                    |         |
| Model          | Voltage (V)  | Air Flow           |         |
|                |              | M <sup>3</sup> /hr | CFM     |
| NA22060HA1B(S) | 100~125      | 900/1000           | 600/700 |
| NA22060HA2B(S) | 200~240      | 900/1000           | 600/700 |
| NA22060HA3B(S) | 380          | 900/1000           | 600/700 |

**NA 22580 Fan**

|               |              |                    |         |
|---------------|--------------|--------------------|---------|
| Size          | 225×225×80mm |                    |         |
| Model         | Voltage (V)  | Air Flow           |         |
|               |              | M <sup>3</sup> /hr | CFM     |
| NA22580HA2B-C | 220          | 1000/1150          | 588/676 |
| NA22580HA3B   | 380          | 1000/1150          | 588/676 |
| NA22580HA6B-C | 380          | 1000/1150          | 588/676 |

**NA 28080 Fan**

|              |              |                    |           |
|--------------|--------------|--------------------|-----------|
| Size         | 280×280×80mm |                    |           |
| Model        | Voltage (V)  | Air Flow           |           |
|              |              | M <sup>3</sup> /hr | CFM       |
| NA28080HA1-C | 100~125      | 2280/2570          | 1341/1512 |
| NA28080HA2-C | 200~240      | 2280/2570          | 1341/1512 |
| NA28080HA3   | 380~420      | 2280/2570          | 1341/1512 |
| NA28080HA6-C | 380~420      | 2280/2570          | 1341/1512 |

## Прозрачное защитное окно



### NTL-AG1002

|      |             |
|------|-------------|
| Way  | 2 Way       |
| Size | 57×100×28mm |



### NTL-AG1003

|      |             |
|------|-------------|
| Way  | 3 Way       |
| Size | 75×100×28mm |



### NTL-AG1004

|      |             |
|------|-------------|
| Way  | 4 Way       |
| Size | 93×100×28mm |



### NTL-AG1006

|      |              |
|------|--------------|
| Way  | 6 Way        |
| Size | 124×100×28mm |



### NTL-AG1008

|      |              |
|------|--------------|
| Way  | 8 Way        |
| Size | 160×100×28mm |



### NTL-AG1010

|      |             |
|------|-------------|
| Way  | 10 Way      |
| Size | 196×95×28mm |




### NTL-AG1012

|      |             |
|------|-------------|
| Way  | 12 Way      |
| Size | 232×95×28mm |




### NTL-AG1013

|      |             |
|------|-------------|
| Way  | 13 Way      |
| Size | 250×95×28mm |



### NTL-AG1016

|      |             |
|------|-------------|
| Way  | 16 Way      |
| Size | 304×95×28mm |




### NTL-AG1018

|      |             |
|------|-------------|
| Way  | 18 Way      |
| Size | 340×95×28mm |



### NTL-AG1086

|      |              |
|------|--------------|
| Way  | 86 Type      |
| Size | 107×130×28mm |



### Fasteners

|      |   |
|------|---|
| Way  | - |
| Size | - |

